



Top Master



AS808

SILICONIZED SEALANT

Siliconeized general purpose sealant with acrylic dispersion with increased mobility and adhesion strength.

PROPERTIES

- Single component, easy to apply,
- After hardening, it is not affected by weather conditions,
- Paintable,
- Odourless,
- Can be used in many porous surfaces,



APPLICATION AREAS

- Indoor and outdoor,
- Expansion joints between prefabricate construction materials,
- Installation of wooden, pvc, iron, aluminium joinery,
- Joints of all kinds of building materials,
- As an insulation material for cracks on walls,
- Sealing of window and door frames,



COLORS

White
(Consult for other colours)



PACKAGING OPTIONS

450 gr, box of 24



TECHNICAL DATA

Appearance	Acrylic dispersion
Application Temperature	+5°C and +30°C
Service Temperature	-20 °C and +70 °C
Density	1,62 ± 0,04 g/cm ³
Tack-Free Time (minutes)	~ 45
Curing Rate	2 mm / 24 hours
Hardness (Shore A)	45-50 ± 3
Elasticity	<%100 ±3

*Technical data are approximate values based on 20°C air temperature and 65% relative humidity.



AS808

SILICONIZED SEALANT



SURFACE PREPARATION

- The surfaces to contact with the sealant must be clean and dry; must be free from oil, dust and rust.
- If there is any applied sealant on the surfaces, it should be removed by mechanical methods.
- Cover the boundaries of the application area with a masking tape. Following the application remove the masking tape immediately.



APPLICATION METHOD

- Fix the cartridge into the gun.
- Apply sealant in a continuous operation, in one direction, applying a positive pressure adequate to properly fill and seal the joint width.
- Due to the smooth consistency of product, dry tooling is recommended.
- Remove the masking tape.
- Excess sealant should be cleaned from the surfaces. After curing, the silicone can only be removed mechanically.



WARNING

- Apply in well-ventilated areas.
- Should not be used in places that are constantly exposed to water.
- Not suitable to be applied outdoors when there is a risk of rain and frost.
- Not suitable for filling dynamic cracks since it is an elastoplastic sealant.
- Should only be painted with elastic paints.



SHELF LIFE AND STORAGE

It should be stored in its closed package, in a cool and dry environment, between +5°C and +25°C. It has a shelf life of 15 months from the date of production.



SAFETY INFORMATION

Contains traces amounts of volatile chemicals. If used indoors, the application area should be well ventilated. Since it may irritate the skin, contact with fresh silicone for long periods should be avoided. Hardened silicone does not contain elements harmful for health. Refer to safety data sheet for detailed information.



ALREDA SEALANTS

Alreda for Import and Export

Management Address
Qalyub, Al-Qalyubia Governorate 6321430 Al-Khedewy-Esmail

+201001764399